

THE BOROUGH OF EDINBORO

BUILDING AND ZONING DEPARTMENT

124 Meadville Street, Edinboro, PA 16412-2502 (814) 734-1812 ext. 130/139 Fax: (814) 734-4492 jrhen@edinboro.net // mjones@edinboro.net

APPLICATION FOR ROAD PERMIT AND BOND

Chapter 21 ~ Streets and Sidewalks

Property Address:	Zoning District:
Parcel ID#: Property Type:	
Owner Address: Email:	
Contractor: Phone: Contractor	
Address: Email:	PA Reg:
Proposed work to be performed:	
Estimated C	Cost of Project:
Please provide a scaled drawing of the property with all proposed cuts into the right of way / road.	
Sewer Lateral: Size // Depth // Cut Width // Backfill // Subbase	// Base // Surface
Water Lateral: Size // Depth // Cut Width // Backfill // Subbase	// Base // Surface
Other: // Size // Depth // Cut Width // Backfill // Subbase _	// Base // Surface
If you have any questions, feel free to contact the Zoning Administrator. I hereby attest I have read the information stated on this application. Furthermore, I attest the information I furnished is true and correct. I understand that the bond shall be held for a period of 18 months from the date of completion of the listed project.	
Owner / Agent	Date
Building & Zoning Department only This project: Complies with O Does not comply with O with the Borough Zoning Ordinances Special Exception O // Conditional Use O // Approved O // Denied O // Additional information requested O	
Permit#: Inv#: Payment: Che	ck/ Cash / Money order / Charge
Building & Zoning Administrator Date	Application Received
CASHTEDED ON:	

§21-102. Street Openings and Pavement Cuts.

1. Permit Required. It shall be unlawful for any person to make any tunnel, opening or excavation of any kind in or under the surface of any street without first securing a permit from the Borough for each separate undertaking; provided, any person maintaining pipes, lines or other underground facilities in or under the surface of any street may proceed with an opening without a permit when emergency circumstances demand the work to be done immediately, provided the permit could not reasonably and practically have been obtained beforehand. The person shall thereafter apply for a permit on the first regular business day on which the Borough office is open for business and said permit shall be retroactive to the date when the work was begun. In all cases where emergency openings are necessary, the Borough Police Department and Borough office shall be notified prior to such opening.

\$21-113. Road Cut Restoration.

In the event a Borough road needs to be cut to gain access to the sanitary sewer main line the following road cut specifications shall be observed:

A. Bonding.

- (1) Connection costs are primarily dependent on size/type of pipe and depth. For the normal size water and sewer line ($\frac{3}{4}$ inch to 6 inches) the current cost is about \$80/per linear foot plus the cost of roadway pavement restoration. This cost can change from time to time per the Borough of Edinboro fee schedule. If the excavation becomes more than routine a review by the Borough Engineer will become necessary which could increase the per foot restoration costs. The contractor will bear all engineering cost at 100 percent.
 - (a) Pavement shall be saw cut for full pavement depth to the width of the trench plus 12 inches on each side.
 - (b) The pavement shall be cut 18 inches beyond the trench limits on both sides to top of base course.
 - (c) Sewer and water lines shall be installed to the requirements of the Municipal Authority of the Borough of Edinboro and the Edinboro Water Authority.
 - (d) Excavated material may be reused as backfill if the material is a granular material meeting PennDOT Publication 408 requirements for 2RC. Otherwise, dispose of offsite and replace with 2RC to sub-base elevation.
 - (e) Backfill shall be compacted in 4-inch lifts or less when using a jumping-jack or 8-inch lifts when using a backhoe tamper attachment to a minimum of 95 percent of the maximum Standard Proctor Density.
 - (f) The top 6 inches of the backfill (sub-base) shall be 2A material meeting the requirements of PennDOT Publication 408, \$350.
 - (g) The sub-base shall be compacted to 100 percent of the maximum Standard Proctor Density.
 - (h) The base course shall be 4-inch BCBC or match the existing, whichever is greater. The material and placement shall follow PennDOT Publication 408 requirements.
 - (i) The surface course shall be 2 inch ID-2 wearing or match existing, whichever is greater. The material and placement shall follow PennDOT Publication 408 requirements.
 - (j) Joints between the pavement and patch shall be sealed using AC-20 material.
 - (k) Pavement shall be maintained for a period of 1 year from restoration. Settling shall be repaired to Borough's satisfaction.
- (2) Cuts in PennDOT rights-of-way are required to have a PennDOT highway occupancy permit. Restoration to PennDOT standards if in conflict with the above.
- (3) For all complex excavations, it may be necessary to employ the Borough Engineer to review said excavation work. These fees are the responsibility of the contractor.

 (Ord. 534, 4/10/2006, \$18-150-B)

Road Bond ~ 20170609 Page **2** of **2**